



Global Traffic
Technologies

Opticom™ Infrared System

Opticom™ Model 794 LED Emitter

An Opticom™ Infrared System Matched Component Product

Description

The Opticom™ Model 794 LED Emitter is a compact, lightweight, weather-resistant encoded signal device intended for use on priority vehicles. The model 794 emitter consists of an LED array with an integral power supply and the required cables. Accessory switch devices are also available. The operation of the device may be customized through its interface software or remote coding unit.

The encoded signal pattern (composed of the individual vehicle class code and vehicle identification number) generated by the model 794 emitter is determined after installation through the use of interface software or remote coding unit.

The model 794 emitter, when installed on authorized service and maintenance vehicles, may also be configured to utilize the automated range-setting feature of Opticom 700 Series Phase Selectors and Opticom 400 Series Discriminators. This feature refines and simplifies individual intersection setup and maintenance techniques.

The model 794 emitter separates precisely-timed pulses of infrared light at the base flash rate of approximately 10 or 14 Hz. It also interleaves programmed encoded pulses that carry the vehicle class and ID number information. These infrared pulses are sensed and processed by other Opticom Infrared system components to cause activation of the system.

The model 794 emitter is capable of being programmed via the model RC790 remote coding unit, eliminating any dependency on a computer. By simply pointing the RC790 at



Opticom™ Model 794 LED Emitter

the model 794 emitter, the user can communicate vehicle class and ID, visible LED, disable mode, diagnostics and default settings with just pushes of a button.

Description of Models

Opticom™ Model 794H LED Emitter:
High-priority emitter

Opticom™ Model 794L LED Emitter:
Low-priority emitter

Opticom™ Model 794T LED Emitter:
Low-priority emitter with reduced output for transit signal priority applications

Opticom™ Model 794R Emitter:
Range-setting emitter for high priority, low priority or probe frequency

An Opticom™ Infrared System Matched Component Product

Opticom™ Model 794 Emitter

Features

- Discrete, penetrating infrared communication
 - Directional
 - Consistent, day and night transmission
 - All-weather performance
- Compact, single source system
- High- and low-priority operation as well as probe-frequency capability
- Encoded signal transmission
 - High priority: 10,000 discrete vehicle IDs (10 classes of vehicles and 1,000 individual codes available within each class)
 - Low priority: 10,000 discrete vehicle IDs (10 classes of vehicles and 1,000 individual codes available within each class)
- Remote range-setting capability
- RS485, J1708 serial interface
- Low power consumption
- CE certified
- SAE J575, SAE J1455 compliant
- Improved installation flexibility
 - Mounts directly on vehicle
- Automatic emitter disable, indicated by slow flashing of the emitter switch's indicator light or emitter's visible LEDs
- Self-diagnostic with visual feedback through the switch's indicator light and visible LED indicator lights
- Cumulative flash counts available through the interface software or RC790 diagnostic mode

Accessories



Opticom™ Switch Models
793B (bottom left),
793S (bottom right),
793R (top right)



Opticom™ RC790 Remote
Coding Unit

- Switches
 - Rocker-type switch for knockout/panel mounting (with simple mounting bracket) (model 793B)
 - Three versions of fully enclosed push-button switches (with dashboard mounting bracket)
 - On/Off only (model 793S)
 - On/Off for high-priority, low-priority and probe frequency with range setting
- Automated range-setting control
- Bezel mount kit
- Programmable via interface software and/or RC790 remote coding unit

	Model 793S Switch	Model 793B Switch	Model 793R Switch	Customer-Supplied Switch
Opticom™ Model 794H LED Emitter	High Priority/Off	High Priority/Off	Not Available	High Priority/Off
Opticom™ Model 794L LED Emitter	Low Priority/Off	Low Priority/Off	Not Available	Low Priority/Off
Opticom™ Model 794T LED Emitter	Low Priority/Off	Low Priority/Off	Not Available	Low Priority/Off
Opticom™ Model 794R LED Emitter	Not Available	Not Available	High Priority/ Low Priority/Off/ Probe Frequency and Range Setting	Not Available

Operating Parameters – Model 794 LED Emitter

- High- or low-priority and probe-frequency operation selected by model and switch combination
- 10,000 vehicle codes available in high priority
- 10,000 vehicle codes available in low priority
- Automated range-setting feature
- Isolated power supply and emitter for positive or negative ground vehicle power system
- Less than 1 amp peak current draw
- Self-diagnostic
- Precisely controlled high-priority flash rate of 14 Hz
- Precisely controlled low-priority flash rate of 10 Hz
- Transmission range up to 2,500 feet (762 m)
- Electrical
 - Input Voltage: 10 to 32 VDC
 - Current: < 1 amp

- Environmental

- Temperature: -30° F (-34° C) to +165° F (+74° C)
- Relative Humidity: 5% to 95%

Physical Dimensions – Model 794 LED Emitter

- **Depth:** 2.25 in. (5 cm)
- **Width:** 5.8 in. (14 cm)
- **Height:** 3.7 in. (9 cm)
- **Weight:** 1.4 lb. (.6 kg)

Physical Dimensions / Operating Parameters Model RC790 Remote Coding Unit

- **Length:** 6.3 in. (16 cm)
- **Width:** 3.7 in. (9.4 cm)
- **Thickness:** 1.0 in. (2.5 cm)
- **Weight:** 0.5 lb. (.2 kg)
- LCD display and a keypad
- Operates on four AAA batteries

Important Notice to Purchaser:

EXCEPT FOR THE LIMITED WARRANTIES SET FORTH IN THIS DOCUMENT, GLOBAL TRAFFIC TECHNOLOGIES (GTT) MAKES NO OTHER WARRANTIES AND EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE.

Global Traffic Technologies (GTT) will, at its sole option, repair, replace or refund any amounts paid for any Opticom™ Infrared System component found to be defective in materials or manufacture within five (5) years from the date of shipment from GTT. See "Warranty and Extended Coverage" for details and limitations of the coverage plan. GTT will provide a functioning replacement component at a standard charge per unit for an additional five (5) years.

GTT warrants future system operability coverage as described herein. The warranties set forth in this document shall not apply to (A) incandescent lamps (confirmation lights) or (B) to any Opticom infrared system components which have been (1) repaired or modified by persons not authorized by GTT; (2) subjected to incorrect installation, misuse, neglect or accident; (3) damaged by extreme atmospheric or weather-related conditions; or (4) subject to events or use outside the normal or anticipated course.

IN NO EVENT SHALL GTT BE LIABLE FOR ANY INJURY (INCLUDING, WITHOUT LIMITATION, PERSONAL INJURY), DEATH, LOSS, OR DAMAGE (INCLUDING, WITHOUT LIMITATION, PROPERTY DAMAGE), WHETHER DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL, OR OTHERWISE, ARISING OUT OF THE USE OR INABILITY TO USE, REPAIR OR FAILURE TO REPAIR, ANY GTT PRODUCT. REGARDLESS OF THE LEGAL THEORY ASSERTED. THE REMEDIES SET FORTH IN THIS DOCUMENT ARE EXCLUSIVE.

Sale and use of the Opticom infrared system is expressly restricted to authorized agencies of government customers, within their specific jurisdictions. However, because the infrared signal generated by the Opticom infrared system is not exclusive, GTT does not warrant exclusive activation by purchaser. Authorized users who desire to use or coordinate use of the Opticom infrared system with that of other jurisdictions must first obtain the prior written approval of each authorized user in the jurisdiction where use is sought.



Global Traffic
Technologies

Global Traffic Technologies, LLC
7800 Third Street North
St. Paul, Minnesota 55128-5441
1-800-258-4610
651-789-7333
www.gtt.com



ISO 9001: 2008
FM 535303

Global Traffic Technologies Canada, Inc.
157 Adelaide Street West
Suite 448
Toronto, ON M5H 4E7
Canada
1-800-258-4610

Opticom and the GTT logo mark are trademarks of
Global Traffic Technologies, LLC.
Used under license in Canada.
Please recycle. Printed in U.S.A.
© Global Traffic Technologies, LLC 2009
All rights reserved.
79-1000-0377-0 (A)